

HARNWOOD COLOUR is a specially developed, high temperature stove paint, formulated for the easiest application. It is fast-drying for use on wood & multi-fuel stoves, boilers, furnaces and traditional cast iron cookers. Once applied it will withstand repeated heating and cooking temperatures up to 600°C.

IMPORTANT NOTICE • ONLY USE IN A WELL VENTILATED AREA WHEN

YOUR STOVE IS COLD This is an interior product and should not be subjected to heavy water or weather exposure out of doors without external high temperature primer.

DIRECTIONS

Before applying observe safety precautions. DO NOT APPLY TO HOT SURFACES. DO NOT SMOKE. Extinguish fires, flames and hot coals. Turn off pilot lights, stoves, heaters, electrical motors and other sources of ignition during use and until all vapours have gone. Surface temperature should be between 15° and 30°C. Reviove ill dust, dirt, rust and grease; scraph off. I see paint from surface. Any glossy paint miss be 'roughened' with sandpaper. Protect surrounding areas from spray mist. Air temperature from 20° to 27°C is optimal for spray opplication. Do not paint at less than 5°C. Shake can vigorously for at least one minute after mixing ball rattles. Point opening of spray button towards object, holding can 30 cm (12") from surface to be painted. Press spray firmly. Use steady, even strokes. Several thin coats give a better finish than one heavy coat. If dogging develops, remove spray button with a twisting motion and clean. DO NOT stick pin or other object into can. Gently replace spray button with a twisting motion with top of can and spray botton pointing away from you. Clean spray button immediately after use by inverting can and pressing spray button until only propellant (no paint) escapes. Discard

empty can in waste bin. DO NOT place in home garbage compactor or burn. DANGER! DO NOT APPLY TO HOT SURFACES • DO NOT SMOKE

Vapours may ignite explosively. Vapour may cause flash fire. Prevent build-up of vapours. Keep away from sparks, flames, or other heat sources. Do not puncture or incinerate container. Exposure to heat or prolonged exposure to sun may cause bursting. Do not expose to heat or store at temperatures above 45°C. Harmful if inhaled. May affect the brain or nervous system causing dizziness,

the brain or nervous system causing dizziness, headaches or nausea. May cause eye, nose, throat and/or skin irritation. Harmful if swallowed. Over-exposure may cause eye damage. To avoid breathing vapours or sproy mists, open windows and doors or use other means to ensure fresh air entry during application, drying and first 3 times stove is burned. Wear suitable protective clothing, gloves and eyelface protection. Avoid contact with skin and eyes. In cose of contact with eyes, rinse immediately with plenty of water and seek medical advice. Intentional misuse by deliberately concentrating and inhaling the

DO NOT SELL TO MINORS • KEEP OUT OF REACH OF CHILDREN

For more information on CHARNWOOD'S products and services please telephone +44 (0) 1983 537780 or visit our website WWW.CHARNWOOD.COM







HIGHLY FLAMMABLE USE WITH EXTREME CARE

CONTENTS 400ml